

Grayson Max: Standards and Features

INTERIOR

Primed Smooth Drywall Throughout
Flat Ceiling Throughout
Smooth Ceiling
8'0" Ceiling Height
Live Wire Carpet Protected with Shaw
Stain Safety
8# Carpet Pad
Tackstrip Carpet Installation
No-Wax Vinyl Floor Coverings by
Congoleum
Recessed 6" LED Lighting
6-Panel Pre-Hung Doors
Mortise Door Hinges
Metal Interior Passage Sets
Door Stops
Smoke Detectors with Battery
Back-Up
Wire Shelving in Guest Closet &
Utility Room
2 1/4" Window & Door Trim
White Painted Mouldings Throughout
Laminate Countertops with Laminate Edging
4" Laminate Backsplash

KITCHEN

Stainless Steel 33x19x7 Sink
Empire Brushed Nickel Single Lever Faucet
USB II Receptacle
Deluxe Free Standing Electric Range

CABINETRY

Evermore Custom Cabinetry
(KCMA Certified)
Hardwood Mission Cabinet Doors w/
Full Overlay
Hardwood Cabinet Face Frames & Stiles
Brushed Nickel Cabinet Hardware
Concealed Cabinet Hinges
Soft Close Cabinet Doors
Dovetail Drawers w/ Soft Close Guides
36" Wall Cabinets with Crouse Crown to
8'0" Ceiling Height
Adjustable Shelves in Wall Cabinets
Adjustable Center Shelf in Base Cabinets
Standard Islands in Most Models

Base Shelf in Vanities
36" High Vanities

BEDROOMS

Switched Receptacles
Egress Window Each Bedroom
Wire Shelves in all Closets
30" Interior Passage Doors
Recessed 4" LED Light in All Walk-In
Closets
Privacy Sets in all Bedrooms

BATHS

60" x 42" Fiberglass Garden Tub w/ Curved
Front and Full Surround in Bath 1
60" One-Piece Fiberglass Tub/Shower
in 2nd Bath
One-Piece Fiberglass Shower with
Glass Door in Glamour Baths
Tub Overflows
1.6 Gallon Per Flush Elongated Toilets
China Stool, Tank and Lid
China Sinks with Overflows and
Pop-Up Drains
Lighted Vent Fan in Each Bath
LED Lights over Vanities
Empire Brushed Nickel Faucets
Anti-Scald Valves on Showers
Privacy Sets in all Bathrooms
In-Wall Toilet Riser

UTILITIES

200 AMP Electrical Service
Arc Fault Circuit Breakers
Plumb and Wire for Washer
Wire and Vent for Dryer
40 Gallon Electric Water Heater with Pan
6-Panel Furnace Door
Air Ready Electric Furnace w/Coil Cabinet
Fiberglass Heat Ducts
Copper Wiring Throughout
Main Water Line Shut-Off Valve
Water Shut-Off Valves -Where Accessible
One Exterior Water Faucet
Uponor Plumbing System
Recessed Dryer Vent Box - Where Available

Grayson Max: Standards and Features

Drain Lines Stubbed Through Floor
Complete Heat System
Insulated Hot Water Lines and P-Traps

INSULATION

R-30 Fiberglass Insulation in Floor
R-19 Fiberglass Insulation in Walls
R-38 Avg. Blown Insulation in Ceiling

EXTERIOR

Patina Lantern Light
at Front Door and Rear Door
Two GFI-Protected Exterior Receptacles
Vinyl Dutch Lap Siding
O.S.B. Sheathing Under Siding
5/12 Roof Pitch
10" or 12" Overhangs & Eaves
(Depending on Model)
Architectural Shingles, 30 Year
Ridgevent Roof Ventilation System
36" Fiberglass 6-Panel Front & Rear
Doors with Deadbolt Locks
Vinyl Insulated Windows with
Low-E Glass
15" Raised Panel Shutters on Front
Door Side
Wind Wrap
Vapor Barrier

CONSTRUCTION 2x10 Floor System with

3/4" T&G O.S.B. Floor Decking

2x6 Exterior Walls

2x4 Marriage Walls

20# Roof Load Design

82 1/2" Window Headers

90 Mile Exposure B Wind Load Design
(VA-TN)

115 Mile Exposure B Wind Load Design
(NC-SC-WV)